



| Specifications                |             | VP1                                                                                          | VP2               |
|-------------------------------|-------------|----------------------------------------------------------------------------------------------|-------------------|
|                               |             | EL-005B-030-7**                                                                              | EL-005B-030-7**-P |
| Product dimensions            | Height(in.) | 14.26"                                                                                       | 14.26"            |
|                               | Width (in.) | 10.01"                                                                                       | 10.01"            |
|                               | Length(in.) | 4.41"                                                                                        | 4.41"             |
| Material                      |             | Aluminum Housing                                                                             |                   |
| Lens Material                 |             | UV Resistant PC Lens                                                                         |                   |
| Rated Wattage                 |             | 30W                                                                                          | 30W               |
| Lumens (Lm)                   |             | 3150Lm                                                                                       | 3150Lm            |
| Lumens Efficacy               |             | 105Lm/W                                                                                      |                   |
| CCT                           |             | 3000K/4000K/5000K/5700K                                                                      |                   |
| CRI                           |             | ≥70                                                                                          |                   |
| Voltage                       |             | 120V-277V                                                                                    |                   |
| Beam Angle                    |             | 90 °                                                                                         |                   |
| Power Factor                  |             | ≥0.8                                                                                         |                   |
| L70 Lumen Maintenance (Hours) |             | 50000                                                                                        |                   |
| Dimming Technology            |             | NO                                                                                           |                   |
| Photocell or Sensor           |             | NO                                                                                           | photocell on/off  |
| Surge Protection              |             | 2.5KV                                                                                        |                   |
| Certifications                |             | ETL、FCC、ROSH                                                                                 |                   |
| Qualifications                |             | DLC                                                                                          |                   |
| Operating Temperature         |             | -40℃ (-40F)~50℃ (+122F)                                                                      |                   |
| IP Rating                     |             | IP65/IK08                                                                                    |                   |
| Warranty                      |             | 5 years                                                                                      |                   |
| Way to install                |             | Wall Mount                                                                                   |                   |
| Application                   |             | Garages/Building lighting/Packing lot lighting/Entryway/Storage warehouses/Security lighting |                   |

**LUMINOUS INTENSITY DISTRIBUTION DIAGRAM**

